

Safety Data Sheet

According to regulation (EU) No. 2015/830 and regulation (EC) No. 1272/2008

Revision date:
12/11/2015

Date of issue:
03/06/2013

Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product Name : MED10-6607
Synonyms : RTV Silicone Dispersion Coating

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : High strength, flowable RTV silicone dispersion coating. For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency telephone number

Emergency : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and
number : Maritime)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2 H319
Skin Sens. 1 H317
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304
Aquatic Chronic 2 H411

Full text of H-phrases: see section 1.6

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : 2-Butanone, O,O',O''-(methylsilylidyne)trioxime, Solvent naphtha, petroleum, light aliphatic, Dibutyltin dilaurate

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

- Precautionary statements (CLP) :
- H304 - May be fatal if swallowed and enters airways
 - H315 - Causes skin irritation
 - H317 - May cause an allergic skin reaction
 - H319 - Causes serious eye irritation
 - H336 - May cause drowsiness or dizziness
 - H373 - May cause damage to organs through prolonged or repeated exposure
 - H411 - Toxic to aquatic life with long lasting effects
 - P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 - P233 - Keep container tightly closed
 - P240 - Ground/bond container and receiving equipment
 - P241 - Use explosion-proof electrical, lighting, ventilating equipment
 - P260 - Do not breathe mist, spray, vapours
 - P264 - Wash hands, forearms, and exposed areas thoroughly after handling
 - P271 - Use only outdoors or in a well-ventilated area
 - P272 - Contaminated work clothing should not be allowed out of the workplace
 - P273 - Avoid release to the environment
 - P280 - Wear eye protection, face protection, protective clothing, protective gloves
 - P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
 - P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 - P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 - P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 - P312 - Call a POISON CENTER or doctor if you feel unwell
 - P321 - Specific treatment (see Section 4 on this SDS)
 - P331 - Do NOT induce vomiting
 - P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 - P337+P313 - If eye irritation persists: Get medical advice/attention
 - P362+P364 - Take off contaminated clothing and wash it before reuse
 - P370+P378 - In case of fire: Use appropriate media to extinguish
 - P391 - Collect spillage
 - P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool
 - P405 - Store locked up
 - P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations

2.3. Other Hazards

Other hazards not contributing to the classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8 (EC no) 265-192-2 (EC index no) 649-267-00-0	50 - 55	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-Butanone, O,O',O''-(methylsilyldiylne)trioxime	(CAS No) 22984-54-9 (EC no) 245-366-4	15 - 20	Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373
Dibutyltin dilaurate	(CAS No) 77-58-7 (EC no) 201-039-8	0,2	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove contaminated clothing. Gently wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Seek medical attention if a large amount is swallowed. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness and dizziness.
- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.
- Chronic symptoms : May cause damage to organs through prolonged or repeated exposure.

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, carbon dioxide, water spray, fog, foam.
Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Will float and can be reignited on water surface.
Explosion hazard : May form flammable/explosive vapour-air mixture.
Reactivity : Hazardous reactions will not occur under normal conditions.

5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Prevent firefighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not breathe gas/vapour/aerosol. Do not get in eyes, on skin, or on clothing. Keep away from heat/sparks/open flames/hot surfaces.
– No smoking. Use special care to avoid static electric charges. Use only non-sparking tools.

6.1.1. For non-emergency personnel

Protective equipment : Use appropriate personal protection equipment (PPE).
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities after a spill.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. When heated, material emits irritating fumes. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Precautions for safe handling : Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, lighting, ventilating equipment.

Storage conditions : Keep in fireproof place. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

Incompatible products : Strong bases. Strong acids. Strong oxidizers.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

High strength, flowable RTV silicone dispersion coating. For professional use only.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tin organic compounds		
Austria	MAK (mg/m ³)	0,1 mg/m ³ (except tri-n-Butyltin compounds-inhalable fraction)
Austria	MAK Short time value (mg/m ³)	0,2 mg/m ³ (except tri-n-Butyltin compounds-inhalable fraction)
Belgium	Limit value (mg/m ³)	0,1 mg/m ³
Belgium	Short time value (mg/m ³)	0,2 mg/m ³
Bulgaria	OEL TWA (mg/m ³)	0,1 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	0,1 mg/m ³ (except Cyhexatin)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	0,2 mg/m ³ (except Cyhexatin)
France	VLE (mg/m ³)	0,2 mg/m ³
France	VME (mg/m ³)	0,1 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0,1 mg/m ³
USA ACGIH	ACGIH STEL (mg/m ³)	0,2 mg/m ³
Spain	VLA-ED (mg/m ³)	0,1 mg/m ³
Spain	VLA-EC (mg/m ³)	0,2 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	0,1 mg/m ³ (except Cyhexatin)
United Kingdom	WEL STEL (mg/m ³)	0,2 mg/m ³ (except Cyhexatin)
Czech Republic	Expoziční limity (PEL) (mg/m ³)	0,1 mg/m ³


MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Tin organic compounds		
Denmark	Grænseværdie (langvarig) (mg/m ³)	0,1 mg/m ³ (except Tri-n-butyltin compounds)
Finland	HTP-arvo (8h) (mg/m ³)	0,1 mg/m ³
Finland	HTP-arvo (15 min)	0,3 mg/m ³
Hungary	AK-érték	0,1 mg/m ³
Hungary	CK-érték	0,4 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	0,1 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	0,2 mg/m ³
Lithuania	IPRV (mg/m ³)	0,1 mg/m ³
Lithuania	TPRV (mg/m ³)	0,2 mg/m ³
Romania	OEL TWA (mg/m ³)	0,05 mg/m ³
Romania	OEL STEL (mg/m ³)	0,15 mg/m ³
Slovakia	NPHV (priemerná) (mg/m ³)	0,1 mg/m ³
Slovakia	NPHV (Hraničná) (mg/m ³)	0,2 mg/m ³
Slovenia	OEL TWA (mg/m ³)	0,1 mg/m ³ (inhalable fraction)
Slovenia	OEL STEL (mg/m ³)	0,4 mg/m ³ (inhalable fraction)
Sweden	nivågränsvärde (NVG) (mg/m ³)	0,1 mg/m ³ (total dust)
Sweden	kortidsvärde (KTV) (mg/m ³)	0,2 mg/m ³ (total dust)
Portugal	OEL TWA (mg/m ³)	0,1 mg/m ³
Portugal	OEL STEL (mg/m ³)	0,2 mg/m ³
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapours may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.
- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Insufficient ventilation: wear respiratory protection. Protective clothing. Protective goggles.
- 
- Materials for protective clothing : Chemically resistant materials and fabrics.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing. Wash contaminated clothing before reuse. Wear fire/flame resistant/retardant clothing.
- Respiratory protection : Use an approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
- Environmental exposure controls : Do not allow the product to be released into the environment.
- Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Appearance	: Translucent
Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 8,9 °C (48 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative Density	: 0,82 (Water=1)
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 50 - 55 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Highly flammable liquid and vapour.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Ignition sources. Direct sunlight. Extremely high or low temperatures. Open flame. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Silicon oxides. Carbon oxides (CO, CO₂). May release flammable gases. Oxides of tin. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapours. Formaldehyd is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Not classified.

Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3000 mg/kg

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

2-Butanone, O,O',O''-(methylsilyldiylidene)trioxime (22984-54-9)	
LD50 oral rat	2463 mg/kg
LD50 dermal rat	> 2000 mg/kg
Dibutyltin dilaurate (77-58-7)	
LD50 dermal rat	> 2 g/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

2-Butanone, O,O',O''-(methylsilyldiylidene)trioxime (22984-54-9)	
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)
Dibutyltin dilaurate (77-58-7)	
EC50 Daphnia 1	0,463 mg/l (Daphnia magna)

12.2. Persistence and degradability

MED10-6607	
Persistence and degradability	Not established.
Dibutyltin dilaurate (77-58-7)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

MED10-6607	
Bioaccumulative potential	Not established.
Dibutyltin dilaurate (77-58-7)	
Log Pow	4,44

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of waste material in accordance with all local, regional, national, and international regulations.

Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Additional information : Avoid release to the environment. Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1268

14.2. UN proper shipping name

Proper Shipping Name (ADR) : PETROLEUM PRODUCTS, N.O.S.

Transport document description (ADR) : UN 1268 PETROLEUM PRODUCTS, N.O.S. (Contains Naphtha), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

Class (ADR) : 3

Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : II

14.5. Environmental hazards

Dangerous for the environment :

Marine pollutant :



Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 33

Classification code (ADR) : F1

Orange plates :



Special provisions (ADR) : 640C, 363

Transport category (ADR) : 2

Tunnel restriction code (ADR) : D/E

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E2

EAC code : 3YE

14.6.2. Transport by sea

MFAG-No : 128

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 50 - 55 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section	Section Header	Change	Date Changed
2.1	Classification of the Substance or Mixture	Removed DSD/DPD information.	12/11/2015
3	Composition/information on ingredients	Removed DSD/DPD information.	12/11/2015
15.1	EU-Regulations	Modified	12/11/2015

Revision date : 12/11/2015

Data sources : According to regulation (EU) No. 2015/830 and regulation (EC) No. 1272/2008

Full text of H- and EUH-phrases

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage

MED10-6607

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

SDS EU (REACH Annex II) 11pt

We believe that the information contained herein is current as of the date of this Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of NuSil Technology, it is the user's obligation to determine the conditions of safe use of the product.



Polymer Systems Technology Limited

Silicone Sales & Services UK - Ireland - Benelux

© 2020 - **Polymer Systems Technology Limited™**

Unit 2. Network 4. Cressex Business Park,
Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: <https://www.silicone-polymers.com>

email: sales@silicone-polymers.co.uk

